



## Dual Block Thermal Cyclers TC-4045D

★★★★★

\$6,650.00

Dual Block Thermal Cyclers TC-4000D Series	Duo Touch Thermal Cyclers	Muti-Block Thermal Cyclers	Thermal cyclers	Thermal Cyclers & PCR Systems
--------------------------------------------	---------------------------	----------------------------	-----------------	-------------------------------

Model

Capacity

Reflectance

Spectrophotometer

RS-1000

Series

Display

Temperature Range

Number of Program

Uniformity

Accuracy

Resolution

Number of Cycle

Holding Temperature variable

Temperature Control

Heating Rate

external

I

Ramping Rate Adjustable

Hot Lid Height Adjustable

Hot Lid Temperature

Power consumption

Steam

Autoclave

ve

TA-300

Series

Overall Dimensions

Digestion,

on,

Distillation &

ion &

Extraction

on

Net Weight

offset

lock

Electrical Requirements

Baths &

Circulators

ors

Catalogue No.

Dual Block Thermal Cyclers TC-4045D has been used in PCR applications in research and

development, food science, pharmaceuticals, life science, animal diagnostics, and analytical laboratories. Features with customized Marlow Peltier heating units and form 4 circuits to control 4 temperature zones with vibrant touch LCD display and maximum ramping rate 5 °C/s. Dual Block Thermal Cyclers TC-4000D accommodates 96×0.2 ml, 60×0.5 ml, Double 48×0.2 ml, 48×0.2 ml + 30×0.5 ml along with 384 well and In-situ plate, this block is completely independently of each other and without interference Fabricated with anodizing technology that have prompt heating conducting and adequate corrosion resistance property.

**Add To Cart**

### Product Description

Dual Block Thermal Cyclers TC-4045D has been used in PCR applications in research and development, food science, pharmaceuticals, life science, animal diagnostics, and analytical laboratories. Features with customized Marlow Peltier heating units and form 4 circuits to control 4 temperature zones with vibrant touch LCD display and maximum ramping rate 5 °C/s. Dual Block Thermal Cyclers TC-4000D accommodates 96×0.2 ml, 60×0.5 ml, Double 48×0.2 ml, 48×0.2 ml + 30×0.5 ml along with 384 well and In-situ plate, this block is completely independently of each other and without interference Fabricated with anodizing technology that have prompt heating conducting and adequate corrosion resistance property.

### Similar Products



Buy Now



Buy Now



Buy Now



Buy Now