



GM-3060



\$1,265.00

Color & Appearance Testing Instruments

Gloss Meter

Low Gloss Meter GM-3000 Series

Low Gloss Meter GM-3060 build with touch screen display, easy to use and easy to measure the gloss of surfaces of materials, portable and has a built-in lithium rechargeable battery. The low gloss meter is equipped with four measurement modes: basic measurement, statistical measurement, continuous measurement, QC measurement. It has 3 angles and measures the low gloss and semi-gloss simultaneously. Certify by international standard ISO 2813, GB/T 9754, ASTM D 523, ASTM D 2457. The function of different modes:

1. Basic mode: For single measurement. The outcomes will be saved automatically. Data used as the standard in Statistic Mode. It can display 5 sets of test data simultaneously.
2. Statistic mode: For multi-measurement of the sample.
3. Continuous mode: For measuring large area samples and evaluate the homogeneity of large-area samples.
4. QC mode: for quality analysis of the sample.
 - 20° = high gloss coatings, plastics, brightened metal, and similar materials
 - 60 ° = medium (semi) gloss coatings, plastics, brightened metal, and similar materials
 - 85° = low gloss coatings, plastics, brightened metal, and similar

[Add To Cart](#)

Product Description

Low Gloss Meter GM-3060 build with touch screen display, easy to use and easy to measure the gloss of surfaces of materials, portable and has a built-in lithium rechargeable battery. The low gloss meter is equipped with four measurement modes: basic measurement, statistical measurement, continuous measurement, QC measurement. It has 3 angles and measures the low gloss and semi-gloss simultaneously. Certify by international standard ISO 2813, GB/T 9754, ASTM D 523, ASTM D 2457. The function of different modes:

1. Basic mode: For single measurement. The outcomes will be saved automatically. Data used as the standard in Statistic Mode. It can display 5 sets of test data simultaneously.
2. Statistic mode: For multi-measurement of the sample.
3. Continuous mode: For measuring large area samples and evaluate the homogeneity of large-area samples.
4. QC mode: for quality analysis of the sample.
 - 20° = high gloss coatings, plastics, brightened metal, and similar materials
 - 60° = medium (semi) gloss coatings, plastics, brightened metal, and similar materials
 - 85° = low gloss coatings, plastics, brightened metal, and similar

Similar Products



Buy Now



Buy Now



Buy Now



Buy Now